

# Product datasheet

Specifications



APC Easy UPS, 2200VA, Tower,  
230V, 4x CEE 7/3 Schuko outlets,  
AVR

BVX2200LI-GR

## Overview

Lead Time Usually in Stock

## Main

Main Input Voltage 230 V AC 1 phase

Main Output Voltage 230 V AC 1 phase

Rated Power In W 1200 W

Rated Power In Va 2200 VA

Input Connection Type Schuko

Output Connection Type 4 Schuko

Cable Length 1.22 m

Number Of Cables 1

Battery Type Lead-acid battery

Provided Equipment User manual

## Batteries & Runtime

Run Time [View Runtime Graph](#)

Efficiency [View Efficiency Graph](#)

Number Of Battery Filled Slots 0

Number Of Battery Free Slots 0

Battery Recharge Time 8 h

Battery Voltage 24 V

Battery Capacity 9.0 Ah

Battery Life 2...3 year(s)

Replacement Battery [APCRBC177](#)

Extended Runtime 0

## General

Max Runtime 240 min

Number Of Power Module Free Slots 0

Number Of Power Module Filled Slots 0

Redundant No

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

---

Ups Size	WS
----------	----

## Physical

---

Colour	Black
Height	19 cm
Width	14 cm
Depth	39 cm
Net Weight	12.2 kg
Mounting Support	Floor
Mounting Preference	No preference
Mounting Mode	Not rack-mountable
Two Post Mountable	0
Usb Compatible	No

## Input

---

Network Frequency	50/60 Hz +/- 5 Hz auto-sensing
Input Voltage Limits	140...300 V 230 V AC
Cos Phi	0.54

## Output

---

Maximum Configurable Power In W	1200 W
Output Frequency	50/60 Hz +/- 1 Hz sync to mains
Ups Type	Line interactive
Wave Type	Stepped approximation to a sinewave
Full Load Runtime	00:01:00 1200 W
Graph Display	1
Half Load Runtime	00:08:30 600 W
Maximum Configurable Power In Va	2200 VA
Transfer Time	6 ms typical : 10 ms maximum

## Conformance

---

Product Certifications	CE CB
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
Equipment Protection Policy	Lifetime : 50000 euros

## Environmental

---

Ambient Air Temperature For Operation	0...40 °C
Relative Humidity	0...95 % non-condensing
Operating Altitude	0...3000 m
Ambient Air Temperature For Storage	-15...40 °C

---

<b>Storage Relative Humidity</b>	0...95 % non-condensing
<b>Storage Altitude</b>	0...3000 m
<b>Acoustic Level</b>	40 dBA
<b>Ip Degree Of Protection</b>	IP20

---

## Surge Protection and Filtering

---

<b>Surge Energy Rate</b>	273 J
--------------------------	-------

---

## Packing Units

---

<b>Unit Type Of Package 1</b>	PCE
<b>Number Of Units In Package 1</b>	1
<b>Package 1 Height</b>	29.7 cm
<b>Package 1 Width</b>	49.5 cm
<b>Package 1 Length</b>	23.5 cm
<b>Package 1 Weight</b>	13.2 kg
<b>Scc14</b>	10731304404627

---

## Contractual warranty

---

<b>Warranty</b>	2 years repair or replace
-----------------	---------------------------

---

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

## Well-being performance

Reach Free Of Svhc

Toxic Heavy Metal Free

Mercury Free

Rohs Exemption Information Yes

## Certifications & Standards

**Reach Regulation**

[REACH Declaration](#)

**Eu Rohs Directive**

Compliant

[EU RoHS Declaration](#)

**China Rohs Regulation**

[China RoHS declaration](#)

Pro-active China RoHS declaration (out of China RoHS legal scope)

**Environmental Disclosure**

[Product Environmental Profile](#)

**Circularity Profile**

[End of Life Information](#)